



MAIN FEATURES:

- Class-leading hydraulic efficiency
- Upgraded unitized mechanical seal
- ECM for simple variable speed control

SPECIFICATIONS & REQUIREMENTS	
Pump Size	4GC
Impeller Diameter	13.5" (34.3 CM)
Motor Power	50 HP (37.3 kW)
Motor Operation	Variable Speed

GENERAL INFORMATION	
Rental Category	Base Mounted Pump
Pump Manufacturer	Bell & Gossett
Pump Model	Series e-1510
Accessories Included	VLT Drive, Triple Duty Valve

OUTPUT	
Design Head / Flow	190' (58 M) / 500 GPM (1,892 LPM)
Max Flow	1,271 GPM (4,810 LPM)
Head @ Max Flow	125' (38.1 M)
MAWP	250 PSIG (17.2 BARG)

DIMENSIONS	
Overall Length	04' 06" (1.4 M)
Overall Width	06' 00" (1.8 M)
Overall Height	04' 06" (1.4 M)
Shipping Weight	1,500 LBS (680 KGS)

CONNECTIONS	
Suction (Input)	5" 250# FLG
Discharge (Output)	4" 250# FLG
Voltage	460 V / 3 Phase / 60 Hz
Amperage	65 A