



### MAIN FEATURES:

- Frame-mounted Shell and Tube Heat Exchanger
- Steam to Hydronic Heat Transfer
- Pre-installed Steam Valving Ready for Use

### GENERAL INFORMATION

Rental Category	Heat Exchanger
Unit Design	RH Internal
Heat Exchanger Design	Shell and Tube
Use Type	Steam – Water

### DIMENSIONS

Overall Length	06' 06" (2.0 M)
Overall Width	06' 00" (1.8 M)
Overall Height	05' 00" (1.5 M)
Shipping Weight	1,500 LBS (680 KGS)

### SPECIFICATIONS & REQUIREMENTS

HX Surface Area	194 FT <sup>2</sup> (18 M <sup>2</sup> )
Design Pressure – Shell	150 PSIG (10.3 BARG)
Design Pressure – Tube	150 PSIG (10.3 BARG)
Max Flow – Tube	1,400 GPM (5,299 LPM)
Voltage (if required)	120 V / 3 Phase / 60 Hz
Amperage (if required)	20 A

### CONNECTIONS

Steam (Input)	4" 150# FLG x 1
Condensate (Output)	2" NPT x 1
HHW Supply (Output)	6" 150# FLG x 1
HHW Return (Input)	6" 150# FLG x 1