

BB-800 BOILER IN A BOX



OUTPUT SPECIFICATIONS	
Operating Range (STM/WTR)	80-235 PSIG (5.5-16.2 BARG)
Turndown (NG / #2 Oil)	10:1/8:1
Steam Quality	99.50%
Efficiency (NG / #2 Oil)	80% - 83% / 85% - 86%

MAIN FEATURES:

- Boiler and Burner Package
- Control Systems and Panels
- Fuel Handling Equipment
- Modulating Feedwater Control Valve
- Blowdown Separator
- Maintenance Accessibility

INPUT SPECIFICATIONS		
City Water	15 GPM @ 50 PSIG (68 LPM @ 3.5 BARG)	
Remote Feed Water	85 GPM @ 265 PSIG (321 LPM @ 18.2 BARG)	
Electricity	480 V / 3 PH / 60 HZ @ 100 A	
Fuel Input (NG / #2 Oil)	33.5 / 32.4 MMBTU/HR (9.8 / 9.5 MW)	
NG Flow	3,348 – 33,480 CFH (1,580 – 15,800 LPM)	
NG Pressure	4.5 - 10 PSIG (0.31 – 0.69 BARG)	
#2 Oil Flow	28.9 – 231.4 GPH (109.4 – 875.9 LPH)	
#2 Oil Pressure	Use Onboard Oil Pump	
Pilot	Propane Tank Included	
Instrument Air (included)	10 CFH @ 100 PSIG (4.72 LPM @ 6.9 BARG)	

GENERAL INFORMATION		
Rental Category	Boiler in a Box	
Boiler Size	800 BHP (7.84 MW)	
Max Output Capacity	27,600 PPH (12.52 T/H)	
Max Pressure (Steam/Water)	250 PSIG (17.2 BARG)	
Fuel(s)	Natural Gas / #2 Oil / Propane	
Service	HPS	
NOx Emission Rating	30 PPM	

DIMENSIONS	
Overall Length	40' 00" (12.2 M)
Overall Width	8' (2.4 M)
Overall Height	13' 06" (4.1 M)
Shipping Weight	70,800 LBS (32,100 KGS)
Operating Weight	86,800 LBS (39,360 KGS)

CONNECTIONS		
Steam Outlet	8" 300# FLG	
Stack Exhaust	24" Ø	
City Water	2" NPT	
Remote Feed Water	2" NPT	
Natural Gas	3" 150# FLG	
#2 Oil Supply	1" NPT	
#2 Oil Return	1" NPT	
Blowdown Drain	6" 150 FLG	
System Drain	2" NPT	
Electrical	2" NPT	



Powerhouse Equipment & Engineering Co. Inc.

1-888-231-4981 | www.powerhouse.com Subject to change without prior notice. Information is for guidance only. Please contact your nearest rental office for detailed application advice.