

800.37.STEAM POWERHOUSE.COM



B-1108

2000 BT-32-360





STANDARDS & CERTIFICATIONS



ASME Section IV



National Board Registered



NFPA-85 Build Standard



Hartford Steam Boiler Inspected

| MANUFACTURER (OEM) | Sellers Engineering Company |
|--------------------|-----------------------------|
| YEAR | 2000 |
| SERIAL NO. | 11458 |
| NATIONAL BOARD NO. | 9403 |
| CRN NO. | - |
| MODEL | BT-32-360 |
| ASME CODE SECTION | Section IV |
| TYPE | Water Heater |
| DESIGN | Single-Pass Firetube |
| MOUNTING | Skid-Mounted |
| INTERNAL | Copper Clad Tubes |
| | |



CAPACITIES & INPUTS

| OUTPUT SERVICE | HHW |
|-------------------------------|-------------------------------|
| OUTPUT CAPACITY | 52.7 GPM @ 100° ΔΤ |
| HORSEPOWER | 75 |
| DESIGN PRESSURE (MAWP) | 150 PSIG |
| OPERATING RANGE | 0 - 150 PSIG |
| HEATING SURFACE | 161 ft ² |
| MAX. FUEL INPUT | 3,200,000 BTU/HR |
| STANDARD FUELS ¹ | Natural Gas & Propane |
| ADDITIONAL FUELS ² | - |
| INPUT GAS PRESSURE | MAX: 10 PSIG MIN: 12" W.C. |
| TURNDOWN RATIOS | 3:1 |
| EMISSION RATING (NOX) | < 50 PPM |
| | |

¹ Standard Fuels: Boiler comes ready to burn these fuels including fuel train, safety devices, integral wiring and delivery systems.

² Additional Fuels: Boiler is capable of runing on these fuels but requires modifications to the burner, fuel delivery systems and wiring, at additional cost.



BURNER AND ELECTRICAL

| BURNER MANUFACTURER (OEM) | Sellers Engineering Company |
|------------------------------|-----------------------------|
| MODEL | Multi Flame |
| ТҮРЕ | Pre-Mix |
| FLUE GAS RECIRCULATION (FGR) | No |
| ELECTRIC | 208V/3PH/60Hz |
| ATOMIZATION | - |
| CONTROL TYPE | Pre-Mix |
| BOILER CONTROL SYSTEM | - |
| BURNER MANAGAMENT SYSTEM | Honeywell RM7840 |
| FLAME SAFEGUARD | IR Scanner |
| BLOW MOTOR | 3 HP |
| BURNER INSTALLED | Yes |
| PILOT TYPE | NG / Propane |
| INSTRUMENT AIR | - |
| AIR COMPRESSOR | - |





DIMENSIONS AND WEIGHTS

| OVERALL LENGTH | 12' 9" |
|------------------|-----------|
| OVERALL HEIGHT | 6' 2" |
| OVERALL WIDTH | 3' 10" |
| SHIPPING WEIGHT | 5,460 LBS |
| OPERATING WEIGHT | 8,000 LBS |
| BOILER OUTLET | 3" NPT |
| BOILER RETURN | 3" NPT |
| EXHAUST OUTLET | 10" x 12" |
| | |



800.37.STEAM

POWERHOUSE.COM

HQ 240 CREEK RD. DELANCO, NJ 08075 USA +1 (856) 764-3333

SOUTHEAST OPERATIONS 1710 PACOLET CT., GASTONIA, NC 28052 USA +1 (704) 864-7707

POWERHOUSE DOES NOT MAKE ANY REPRESENTATIONS, WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED WITH THIS BOILER SPECIFICATION SHEET. THE CONTAINED INFORMATION IS PROPRIETARY TO POWERHOUSE AND NO OWNERSHIP RIGHTS ARE HEREBY TRANSFERRED. NO PART OF THE SHEET SHALL BE USED, REPRODUCED, TRANSLATED, CONVERTED, ADAPTED, STORED IN A RETRIEVAL SYSTEM, COMMUNICATED OR TRANSMITTED BY ANY MEANS, FOR ANY COMMERCIAL PURPOSE, INCLUDING WITHOUT LIMITATION, SALE, RESALE, LICENSE, RENTAL OR LEASE, WITHOUT THE PRIOR EXPRESS WRITTEN CONSENT OF POWERHOUSE. NEITHER POWERHOUSE NOR ANY OF ITS DIRECTORS, OFFICERS, EMPLOYEES OR AGENTS SHALL BE LIABLE BASED ON CONTRACT, WARRANTY, STRICT LIABILITY OR NEGLIGENCE, PATENT INFRINGEMENT, TORT OR IN ANY OTHER MANNER WHATSOEVER TO ANY PERSON FOR ANY LOSS, DAMAGE, INJURY, LIABILITY, COST OR EXPENSE OF ANY NATURE, INCLUDING WITHOUT LIMITATION INCIDENTAL, SPECIAL, INDIRECT, DIRECT, LIQUIDATED, EXEMPLARY, PUNITIVE OR CONSEQUENTIAL DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE SPECIFICATION SHEET.



PLEASE CONTACT POWERHOUSE AT 856-764-3333 OR 1-800-37-STEAM FOR ENGINEERED DRAWINGS AND COMPLETE OGM MANUALS.