

UNIT UNDERGOING REFURBISHMENT

COMPLETED IMAGES COMING SOON

POWERHOUSE

B-983

2012 S5-GP2-60-150





STANDARDS & CERTIFICATIONS



ASME Section I



National Board Registered



NFPA-85 Build Standard



Hartford Steam Boiler Inspected

MANUFACTURER (OEM)	Hurst
YEAR	2012
SERIAL NO.	S300-150-63
NATIONAL BOARD NO.	18149
CRN NO.	M8932.5
MODEL	S5-GP2-60-150
ASME CODE SECTION	Section 1
ТҮРЕ	Scotch
DESIGN	Four-Pass Wetback Firetube
MOUNTING	Saddles & Skid-Mounted
INTERNAL	Plain Furnace & Straight Tubes



CAPACITIES & INPUTS

OUTPUT SERVICE	HPS
OUTPUT CAPACITY	2,070 LB/HR
HORSEPOWER	60 BHP
DESIGN PRESSURE (MAWP)	150 PSIG
OPERATING RANGE	90 - 135 PSIG
HEATING SURFACE	300 ft ²
MAX. FUEL INPUT	NG: 2,520,000 BTU/HR #2: 18 GAL/HR
STANDARD FUELS ¹	Natural Gas & #2 Fuel Oil
ADDITIONAL FUELS ²	
INPUT GAS PRESSURE	MAX: 1.0 PSIG MIN: 14 IN WC
TURNDOWN RATIOS	NG: 2.5:1 #2: 1.6:1
EMISSION RATING (NOX)	NG: 80 PPM #2: 135 PPM

¹ Standard Fuels: Boiler comes ready to burn these fuels including fuel train, safety devices, integral wiring and delivery systems.

² Additional Fuels: Boiler is capable of runing on these fuels but requires modifications to the burner, fuel delivery systems and wiring, at additional cost.

BURNER AND ELECTRICAL

BURNER MANUFACTURER (OEM)	Webster
MODEL	JB2C-07
ТҮРЕ	Modulation
FLUE GAS RECIRCULATION (FGR)	No
ELECTRIC	480V/3Ph/60Hz
ATOMIZATION	Pressure
CONTROL TYPE	Single-Point Positioning
BOILER CONTROL SYSTEM	-
BURNER MANAGAMENT SYSTEM	Honeywell RM7840L
FLAME SAFEGUARD	UV Scanner
BLOW MOTOR	0.75 HP
BURNER INSTALLED	Yes
PILOT TYPE	Propane (LPG), NG, Spark
INSTRUMENT AIR	-
AIR COMPRESSOR	-



DIMENSIONS AND WEIGHTS

OVERALL LENGTH	11' 5"
OVERALL HEIGHT	5' 6-5/8"
OVERALL WIDTH	5' 6"
SHIPPING WEIGHT	6,450 LBS
OPERATING WEIGHT	9,600 LBS
BOILER OUTLET	2-1/2" NPT
EXHAUST OUTLET	12" ø OD

800.37.STEAM

POWERHOUSE.COM

HQ 240 CREEK RD. DELANCO, NJ 08075 USA +1 (856) 764-3333

SOUTHEAST OPERATIONS 1710 PACOLET CT., GASTONIA, NC 28052 USA +1 (704) 864-7707

POWERHOUSE DOES NOT MAKE ANY REPRESENTATIONS, WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED WITH THIS BOILER SPECIFICATION SHEET. THE CONTAINED INFORMATION IS PROPRIETARY TO POWERHOUSE AND NO OWNERSHIP RIGHTS ARE HEREBY TRANSFERRED. NO PART OF THE SHEET SHALL BE USED, REPRODUCED, TRANSLATED, CONVERTED, ADAPTED, STORED IN A RETRIEVAL SYSTEM, COMMUNICATED OR TRANSMITTED BY ANY MEANS, FOR ANY COMMERCIAL PURPOSE, INCLUDING WITHOUT LIMITATION, SALE, RESALE, LICENSE, RENTAL OR LEASE, WITHOUT THE PRIOR EXPRESS WRITTEN CONSENT OF POWERHOUSE. NEITHER POWERHOUSE NOR ANY OF ITS DIRECTORS, OFFICERS, EMPLOYEES OR AGENTS SHALL BE LIABLE BASED ON CONTRACT, WARRANTY, STRICT LIABILITY OR NEGLIGENCE, PATENT INFRINGEMENT, TORT OR IN ANY OTHER MANNER WHATSOEVER TO ANY PERSON FOR ANY LOSS, DAMAGE, INJURY, LIABILITY, COST OR EXPENSE OF ANY NATURE, INCLUDING WITHOUT LIMITATION INCIDENTAL, SPECIAL, INDIRECT, DIRECT, LIQUIDATED, EXEMPLARY, PUNITIVE OR CONSEQUENTIAL DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF THE SPECIFICATION SHEET.



PLEASE CONTACT POWERHOUSE AT 856-764-3333 OR 1-800-37-STEAM FOR ENGINEERED DRAWINGS AND COMPLETE OGM MANUALS.